

GUARANTEED TECHNICAL PARTICULARS - 11 KV 'V' CROSSARM

Sl. No.	P A R T I C U L A R S	
1	Type of Crossarm	"V" type
2	Grade of Steel	43A Mild Steel
3	Steel Standard	IS : 2062/1992
4	Fabrication Standard	IS : 802/1978
5	Dimension	As per drawing
6	Steel Section to be used	ISMC - 75mm x 40mm x 6mm Flat - 50mm x 6mm
7	Standard of Galvanisation	Hot-dipped galvanisation as per IS : 2629/92
8	Weight of M.S Channel per meter.	6.8 kg
9	Minimum strength of M.S Channel.	As per IS : 808 (Revised)
10	Minimum Average mass of zinc coating.	610 gm/sq. Mtr. (IS : 4759/1979)
11	Uniformity of zinc coating.	As per IS : 2633/1986.

Please quote for both MS & GI

GUARANTEED TECHNICAL PARTICULARS - LTCROSSARM, 3 Phase, 4 Wire

Sl. No.	P A R T I C U L A R S	
1	Type of Crossarm	LT Crossarm, 3 Phase 4 Wire
2	Grade of Steel	43A Mild Steel
3	Steel Standard	IS : 2062/1992
4	Fabrication Standard	IS : 802/1978
5	Dimension	As per drawing
6	Steel Section to be used	ISMC - 75mm x 40mm
7	Standard of Galvanisation	Hot-dipped galvanisation as per IS : 2629/92
8	Minimum Average mass of zinc coating.	610 gm/sq. Mtr. (IS : 4759/1979)
9	Uniformity of zinc coating.	As per IS : 2633/1986.

Please quote for both MS & GI